

ELDY THRUSTER (80/06)




FEATURES

- Compact, light weight and elegant design.
- Reliable and maintenance free operation.
- Smooth jerk free perfectly linear motion.
- Low noise and does not emit electrical disturbance.
- Suitable for out-door installation.
- Low power input.
- Easy mounting and dismounting.
- Bi-directional operation.
- Immune from external over-loading.
- Immune from supply voltage variations.


TECHNICAL DATA

THRUSTER MODEL	ELD 80/06
LIFTING FORCE	80 Kg / 800 N
STROKE	60 mm
CURRENT AT 415 VAC 50 HZ	1.2 Amps
POWER	380 Watt
OIL CAPACITY	4.5 Liters
WEIGHT	21 Kg
VOLTAGE	400 / 440 VAC, 3Ø
INGRESS PROTECTION	IP-65 IS/IEC 600529:2001
NO. OF START	720/ Hr
AMBIENT TEMPERATURE	-25°C + 50°C
INSULATION	Class F


★ 380V, 460V, 550V on Enquiry



**ELECTRO-HYDRAULIC THRUSTER
MODEL ELD 80/06**



SECTIONAL VIEW



ELD 80/06

H. O. Unit - I : C-15/16, Nand Jyot
Industrial Estate, Andheri-Kurla
Road, Mumbai - 400072,
Tel : (022) 42469700/730
E-mail : sales@socgroup.in

Unit - II : Plot No. 4912, G. I. D. C.,
Phase IV, Vatva,
Ahmedabad - 382445
Tel.: (079) 68169700/702/712
E-mail : enquiry2@socgroup.in

Visit us at :
www.speedocontrols.com
www.socremote.com

**SPEED-O-CONTROLS
PVT. LTD.**
CRANE CONTROL GEAR